

RETOL

Best Quality & Customer Satisfaction Power Booster



SHRESHTH INFRA SOLUTIONS PVT. LTD.

First Floor KH Plot No. 2A, Kehar Singh State, Saidulajb Village,
Lane No. 2, New Delhi-110030 South Delhi

Website: www.retolindia.com

RETOL POWER 4T 20W-40 MEET API SN : JASO MA-2

Description : RETOL POWER 4-T 20W- 40 is a semi synthetic 4 stroke multi-grade engine oil specially formulated for 4 stroke motorcycle engines. The high quality formulation and specially balanced additive package ensures compatibility with all components, including wet clutch and oil lubricated couplings, and offers optimum lubrication throughout all conditions and temperatures.

TECHNICAL CHARACTERISTICS AND FEATURES

- Very good shear stability
- Excellent cold start characteristics High oxidation stability
- Excellent viscosity-temperature behaviour Suitable for use in catalyst-equipped machines
- Exceptional detergent and dispersant characteristics ensures cleaner engines
- High safety reserves even under extreme conditions

Semi Synthetic



Bike Oil

Pack Sizes :- 900 ml, 1, 50 & 210 ltr.



RETOL 4T 20W-40 MEET API SL : JASO MA-2

Description : RETOL 4-T 20W-40 is the premium quality motor cycle engine oil made to cater to the highly demanding lubrication requirements of modern 4-Stroke geared bikes. is manufacturer from the good quality of base oil and Additive technology to meet the most stringent requirements of API SL as well as JASO MA 2. RETOL 4 - T 20W-40 provides superior protection for engine, clutch and gears of a motor cycle which helps you to derive the best performance from your bike all the time, while ensuring high engine durability.

Features & Benefits :

- High engine durability
- High fuel efficiency
- Low oil consumption
- Lower maintenance cost
- Longer oil and engine life

Semi Synthetic

Pack Sizes :- 800 ml, 900 ml, 1, 50 & 210 ltr.

Bike Oil

RETOL GOLD 4T 20W-40 JASO MA-2 SM

Description : RETOL GOLD 4 - T is premium 4-stroke motorcycle engine oil which is specially designed to give Longer Engine Life. Its engine protection properties are developed using RETOL expertise in international Grand Prix Racing.

Applications : RETOL GOLD 4 - T is formulated with Prolife Technology, which ensures longer engine Life by preventing metal-to-metal contact even under extreme condition.



Bike Oil

Pack Sizes :- 900 ml, 50 & 210 ltr.



RETOL ACTIVE 4T 20W-40 JASO API SL

Description : A motorcycle engine is at risk of damage when it's warming up, running normally and even when turned off. There are over 10 million instances per month where a motorcycle-engine could be damaged. RETOL Active 4T 20w40 has improved Actibond™ molecules that cling firmly to the engine to provide Continuous Protection through all stages of the ride, and beyond: Start up, Running and Stop.

Application : RETOL Active 4T 20w40 is suitable for all 4-Stroke motorcycle engines where API SL (and below) and or JASO API SL specifications are recommended.

Pack Sizes :- 900 ml, 1, 50 & 210 ltr.

Bike Oil

RETOL PLUS 4T 10W-30 JASO SM

Description : RETOL OIL 4T Plus is a high quality SAE 10w30 engine oil developed specially for the latest high performance air & water cooled 4-stroke motor cycle engines blended from the highest quality base oil and high performance additive. It provides excellent protection and ensures long engine life.

Suitable for use in Engine where JASO SJ grade required.

Also available in
800 ml 10W30



Bike Oil

Pack Sizes :- 900 ml, 50 & 210 ltr.



RETOL 20W-40 4T MEET BY API SM JASO

Description : Most engine wear happens during engine warm up. ordinary engine oils drain off engine parts when the stops, leading to wear during warm up. Rodex uniquely formulated with molecules clings to engine parts even when engine switched off, providing protection from the engine starts.

Suitable for use in Engine where JASO SL grade required.

Pack Sizes :- 900 ml, 1 & 210 ltr.

Bike Oil

RETOL 20W-50 API SL

Description : A motorcycle engine is at risk of damage when it's warming up, running normally and even when turned off. RETOL API 20W50 has improved Actibond™ molecules that cling firmly to the engine to provide Continuous Protection through all stages of the ride, and beyond: Start up, Running and Stop.

Application : RETOL API 20W50 is suitable for all 4-Stroke motorcycle engines where API SL (and below) and or JASO MA-2 and MA specifications are recommended.



Car & CNG Oil

Pack Sizes :- 1, 3, 3.5, 5, 7.5, 10, 20 & 210 ltr.

RETOL CI 4 15W-40 MEET BY API CI-4

Description: RETOL OIL is SAE 15W40 high quality mixed fleet engine oil recommended for use in all engines, both on and in a wide range of diesel engines. POWERUP 15W40 has been designed to provide superior soot dispersancy, exceptional cleanliness and reduced oil consumption through the use of a unique combination of selected additives and base oils, and is suitable for use in normally aspirated and turbo charged diesel engines.

Application : RETOL Oil 15W40 is recommended for use where the following specifications and classifications are required. SAE 15W-40 API CI-4

Performance Benefits : • RETOL 15W40 reduces maintenance and fleet operating costs. • Extended equipment life. • Improved soot dispersancy will ensure a cleaner engine. provides optimum performance at all times. • Controls bore polish and oil consumption. • Continues to act efficiently for a longer time period than generally expected.



Pack Sizes :- 500 ml, 1, 3, 3.5, 5, 7.5, 10, 15, 20, 50 & 210 ltr.

Car & Truck Oil



RETOL TURBO 15W-40 CH-4

Description : RETOL Turbo CH-4 Oil 15W-40 is a high performance diesel engine oil that provides proven protection of diesel engines operating in severe conditions for both on and Off-highway applications. RETOL Turbo CH-4 Oil 15W-40 is primarily intended for use in diesel commercial Vehicles. The technology in RETOL Turbo CH-4 Oil 15W-40 delivers excellent performance in both modern diesel engines as well as older models.

Applications : RETOL Turbo CH-4 oil 15W-40 is primarily intended for use in diesel commercial vehicles. the technology in RETOL Turbo CH-4 oil 15W-40 delivers excellent performance in both modern diesel engines as well as older models.

Diesel Auto Oil

Pack Sizes :- 1, 3, 3.5, 5, 7.5, 10, 15, 50 & 210 ltr.



RETOL COOLANT 20W-40 MEET BY 1:4

Description : Radiator coolant is mixed with water to keep the radiator from freezing in extreme cold and overheating in extreme heat

Use : Fill 1 Liter Super RETOL COOLANT After Add 3 Liter Best Quality Water.

Benefits : Keep Engine Cooler. Lubricates of Circulation Pump. Make Long Life of Engine Oil. System's All Metal Protestant. Not Choking Radiator System.

Pack Sizes :- 1, 3, 5, 20 & 210 ltr..

Coolant



RETOL TURBO 15W-40 CH-4

Description : RETOL Turbo CH-4 Oil 15W-40 is a high performance of diesel engines operating in severe conditions for both on and Off-highway applications. RETOL Turbo CH-4 Oil 15W-40 is primarily intended for use in diesel commercial Vehicles. The technology in POWERUP Turbo CH-4 Oil 15W-40 delivers excellent performance in both modern diesel engines as well as older models.

Applications : RETOL Turbo CH-4 oil 15W-40 is primarily intended for use in diesel commercial vehicles. the technology in RETOL Turbo CH-4 oil 15W-40 delivers excellent performance in both modern diesel engines as well as older models.

Diesel Auto Oil

Pack Sizes :- 1, 3, 3.5, 5, 7.5, 10, 15, 50 & 210 ltr.

RETOL GEAR EP 90 MEET API GL-4

Description : RETOL GEAR GL-4 EP-90 OIL is a high quality, Extreme Pressure type gear and transmission oil suitable for use in cars, Trucks, Buses Construction Equipment, farm equipments and industrial application,. This oil meets high performance requirements of American Petroleum Institute API GL-4 EP 90 NO. US Military specification Used as factory fill by many gearmakers.

Benefits : • Fuel economy • Longer component life • Outstanding all performance



Pack Sizes :- 1, 5, 10, 20, 50 & 210 ltr.

Automotive Gear Oil

RETOL HYDRAULIC OIL

Description : RETOL HYDRAULIC OIL range are based upon mineral oil enhanced with a stabilised zinc additive system.

Application : RETOL HYDRAULIC OIL is primarily for use in hydraulic equipment, but is suitable for other duties in which lubricants with good oxidation stability and lubrication performance are required. The quality of its base oils and additives permits the application of the RETOL HYDRAULIC OIL range in lightly loaded gears and for use as circulating oil in applications where a rust and oxidation inhibited oil is required.

RETOL HYDRAULIC OIL meet the specification requirements of the Vickers vane pump test, DIN 51524 Part 2 and is classified as DIN 51502 classification – HLP & ISO 6743/4 – Hydraulic Oils Type HM. The range is fully compatible with elastomer materials commonly used for static and dynamic seals, such as nitrile, silicone and fluorinated (e.g. Viton) polymers.



Hydraulic Oil

Pack Sizes :- 5, 10, 20, 26, 50 & 210 ltr.

RETOL AP 3 GREASE (WHITE & RED GEL)

Description : RETOL AP3 GREASE is all purpose lubricating grease, manufactured from well defined base oils with selective additives to obtain the following properties.

Application : RETOL AP3 GREASE is used for the lubrication of ball and roller ball bearings, wheel bearings included and also applicable of lubricating universal joints and chassis pivots of vehicles.

Performance Benefits : • Great adhesion to metals • Excellent water displacing capacity • Very good stability • Very effective against wear and corrosion • Very good pumping qualities

Recommended For : Cars / Vans / Motorcycle / Scooters, Mopeds, Quads (ATV) / Trucks & Buses / Agricultural Tractors / Industrial Machines



Pack Sizes :- 100 gm, 250, 500, 1, 2, 3, 5, 10, 18, 50, 180 kg.

Grease



RETOL CHASSIS GREASE

Description : RETOL CHASSIS GREASE is premium quality calcium based automotive grease manufactured from superior quality base stocks and specially selected additives. RETOL CHASSIS GREASE is having moderately high drop points, resistance to oxidation, good thermal and structural stability. This grease also provides protection against rust and corrosion.

Application : RETOL CHASSIS GREASE an ideal product for lubrication of chassis of all types of Tractors, Heavy duty equipment, Passenger, Automotive vehicles and other commercial.

Grease

Pack Sizes :- 500 gm, 1, 3, 5, 10, 18, 50 & 180 kg.



Manufacturing & Marketing by
SHRESHTH INFRA SOLUTIONS

Automotive & Industrial Lubricant

We deal in the following :
Lubricants Including Engine Oil & Industrial Oil
Grease & Other Lubricant Solutions.

Website : www.retolindia.com, Email : retolindia@gmail.com